

## Specification

Size		483 x 133 x 294 mm (19 x 5.25 x 11.5 ins)
Weight		9.5kg (21lbs)
Enclosure material		Aluminium alloy
Mounting		Rack mounted (3u format)*
Channels		16 per rack
Inputs	Gas	2 or 3 wire, 4-20mA (sink or source) or mV bridge
	Fire - smoke detectors, heat detectors and manual call points, up to 20 per loop	Maximum 32 loops per rack (ie 16 twin zone fire modules)
Outputs	Analogue	16 x 4-20mA, max load 960 Ohms or 1-5 V, min. load 100 Ohms
	External audible/visual alarm drive	Powered 24 V dc, max load up to 200mA for each alarm level
Relays	Type	Up to 84 DPCO, contacts rated 5 A @ 250 V ac, non-inductive load
	Assignment - common - per channel - voting	Alarm 1, Alarm 2, Alarm 3, Fault Gas alarms 1, 2, & 3, fire & fault Up to 16, configurable
	Relay modes	Energised / de-energised & latching, non-latching
Digital communication		RS232 with PanelsPro or SetGMon only
Logging		Built-in datalogger - data available via PanelsPro or SetGmon
Panel indication	Channel number Gas reading Measurement units System fault	4 lines x 20 characters back-lit LCD On main LCD plus green LED bar-graph on channel card ppm, %LEL, %vol, fire yellow LED
Alarm indication	Audible-internal sounder Visual - alarm - fault - inhibit	As standard 3 individual & 3 common alarms (red LED) Individual and common fault (yellow LED) Individual inhibit (yellow LED)
Power	AC mains DC Battery back-up	100-260 V ac 50/60 Hz external 27.6 V dc External
Remote accept/reset		As standard
Lamp test		As standard
Approvals	Low voltage directive EMC Directive ATEX	Meets BS EN 61010-1 Meets EN 50082-1, EN 50081-1, EN 50270, EN61000-6-4 Conforms to EN60079-25 in configuration with Zener Barrier Baseefa 05Y0090/1
Operating temperature		0°C to +50°C (32°F to 122°F)
Humidity		0-95% non-condensing

\* Wall-mounted and floor-standing cabinets are optional, dimensions on request.

### Disclaimer

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement Crowcon Detection Instruments Limited reserves the right to make product changes without notice. The products are routinely subject to a programme of testing which may result in some changes in the characteristics quoted. Technical information contained in this document or otherwise provided by Crowcon are based upon records, tests, or experience that the company believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed.

Many factors beyond Crowcon Detection Instruments' control and uniquely within user's knowledge and control can affect the use and performance of a Crowcon product in a particular application.

As the products may be used by the client in circumstances beyond the knowledge and control of Crowcon Detection Instruments Limited, we cannot determine the relevance of these to an individual customer's application. It is the clients' sole responsibility to carry out the necessary tests to evaluate the usefulness of the products and review all applicable regulations and standards to ensure their safety of operation in a particular application.

**CROWCON**  
Detecting Gas Saving Lives

# Gasmonitor Plus

## Gas Detection Control Panel

- Gas and fire monitoring
- Modular input cards
- Easy push-button operation
- Expandable rack based solution
- Optional battery backup



**CROWCON**  
Detecting Gas Saving Lives

Crowcon reserves the right to change the design or specification of the product without notice.  
© 2019 Crowcon Detection Instruments Ltd. Copyright to some photographs held separately.

www.crowcon.com

# Gasmonitor Plus

## Gas Detection Control Panels

### Choosing the Control Panel for your needs

Gasmonitor Plus is our flexible microprocessor-controlled system designed with a modular approach, so you get exactly what you want. Used across the globe, both on and offshore, Gasmonitor Plus provides the cost-effective solution to your system requirements.



### Features

#### Fixed systems for gas and fire monitoring

Gasmonitor Plus is our flexible microprocessor-controlled system designed with a modular approach, so you get exactly what you want. Used throughout the world, both on and offshore, Gasmonitor Plus provides the cost-effective solution to your system requirements. Gasmonitor Plus, the gas and fire control system you can trust.

#### Simple to use

Gasmonitor Plus offers flexibility while still providing simple operation. All the day to day functions are accessible via push buttons on the front panel. As well as a rolling display, indicating the channel currently monitored, each channel has a bar graph display. This unique bar graph format is ranged to indicate readings below the first alarm setting, providing an instantaneous representation of the gas concentration on every detector. Common alarm LEDs on the display card and individual alarms on the panel only light when a hazard or fault is detected. This means the whole rack status can be checked at a glance.

#### Flexible architecture

Each channel has three levels of alarm as well as a dedicated analogue output, set as 4-20 mA as standard. Optional relay modules can interface to the panel to provide up to a total of 84 output relays per rack. Sixteen of these relays can be configured/voted from a combination of the three levels of alarm per channel. The RS232 digital interface provides connectivity with PC for configuration and datalog upload. Each rack is uniquely addressable, making multi-drop architectures possible. This cuts down on configuration.

#### Proven in-use

Gasmonitor Plus is a microprocessor-based expandable control system, which can be multiplied to offer unlimited channels and outputs. Its modular construction provides ultimate customisation capacity with minimum wiring.

### Key elements

Industry-standard gas detectors	Remote reset switch
Analogue outputs per channel - 4-20mA or 1-5Vdc	AC/DC Power options
Dedicated external audio/visual alarm drive	Optional voted relays
Dual channel, with up to 20 smoke/heat detectors per zone	Optional battery backup
Common and individual channel relays for levels 1, 2, 3 and fault with voting relay option	

