

F-Gas

Fixed Point Gas Detectors

Long life IR sensor

Highly reliable

Low maintenance costs



F-Gas

Refrigerant Gas and SF₆ Detector

The Crowcon F-Gas detector is a high quality infrared (IR) fixed-point detector that delivers dependable detection of freon gases. Available for detecting a range of different refrigerant gases and also sulphur hexafluoride (SF₆), the Crowcon F-Gas detector can be connected to any control system that accepts an analogue signal.

Housed within an IP54 rugged enclosure, the F-Gas detector is suitable for use in non-hazardous areas such as plant rooms or switchgear rooms. In addition to protecting personnel from toxic gas risks, installing the F-Gas detector also helps to reduce the risk of leakage of powerful 'greenhouse gases' into the environment.



Refrigerant gas options

Blended fluids used in refrigeration/ air conditioning market:

Refrigerant	Components	Measuring range
R404a	R143a/125/134a	1000 ppm
R407a	R32/125/134a	1000 ppm
R407c	R32/125/134a	1000 ppm
R410a	R32/125	1000 ppm
R507	R143a/125	1000 ppm

Pure fluids

Fluids	Formula	Name	Measuring range
HCFC 22 (R22)	CHClF ₂	Chlorodifluoromethane	1000 ppm
HCFC 123 (R123)	CHCl ₂ CF ₃	2,2-Dichloro-1,1,1-trifluoroethane	1000 ppm
HFC 125 (R125)	C ₂ HF ₅	Pentafluoroethane	1000 ppm
HFC 134a (R134a)	CH ₂ FCF ₃	1,1,1,2-Tetrafluoroethane	1000 ppm

Special fluidity used for vehicle refrigeration

Fluid	Formula	Name	Measuring range
R1234yf	CH ₂ =CF ₃	Tetrafluoropropene	1000 ppm

Insulating gas

Gas	Name	Measuring range
SF ₆	Sulphur hexafluoride	1000 ppm

Accurate and reliable

Superior IR sensor technology

Provides fast, stable and dependable performance with low maintenance and long life. Unlike cheaper semi-conductor type sensors the F-Gas detector is not affected by other types of gas or changes in temperature or humidity.

Simple and versatile

LED indicators

Tri-coloured LED's indicate the operating status of the detector, and in combination with the function keys, facilitate simple adjustments such as zero and calibration.

Choice of output signals

The analogue output signal can be set as 4-20mA, 0-20mA, 0-2V, 0-5V or 0-10Vdc for compatibility with virtually any control system.

Long life with low maintenance costs

No consumable parts

Provides many years of service with no requirement to replace the sensor or any other components.

Simple to test

Requires a bi-annual gas check only. Re-calibration is only necessary if readings are out of range.

IP54 rated enclosure

Provides good protection from dust and water ingress in indoor environments.

Safety and compliance

F-Gas regulations compatible

Enables F-Gas suppliers and users to comply with the mandatory European F-Gas regulations.

Rapid gas leak detection

Provides an early warning that gas is leaking and thus maintains system efficiency and reduces expensive gas replacement costs.

Environmental protection

Helps to reduce the risk of leakage of powerful 'greenhouse gases' into the environment.

Specification

Size	151 x 80 x 60mm (5.9 x 3.1 x 2.4ins) (Total size with cable gland: 151mm x 102mm x 60mm)
Weight	0.25kg (8.8oz)
Ingress protection	IP54
Measuring principle	Non-dispersive infrared (NDIR)
Range	0-1000ppm
Resolution	1 ppm
Power	12-28Vdc
Analogue output	4-20mA current source (can be set to 0-20mA, 0-2V, 0-5V or 0-10V)
Operating temperature	-20 to +40°C
Humidity	0-95% RH non-condensing
Repeatability	+/- 1% FSD
Linearity	+/- 2% FSD
Start up time	<120 seconds
Response time	30 seconds approximately
Pressure	800-1200mBar
Approvals	EMC: EN50270

This product is designed for non-hazardous area operation only

Disclaimer

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement Crowcon Detection Instruments Limited reserves the right to make product changes without notice. The products are routinely subject to a programme of testing which may result in some changes in the characteristics quoted. Technical information contained in this document or otherwise provided by Crowcon are based upon records, tests, or experience that the company believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed.

Many factors beyond Crowcon Detection Instruments' control and uniquely within user's knowledge and control can affect the use and performance of a Crowcon product in a particular application.

As the products may be used by the client in circumstances beyond the knowledge and control of Crowcon Detection Instruments Limited, we cannot determine the relevance of these to an individual customer's application. It is the clients' sole responsibility to carry out the necessary tests to evaluate the usefulness of the products and review all applicable regulations and standards to ensure their safety of operation in a particular application.