

Tetra 3

Specialist Four Gas Personal Monitor

Rugged

Wide range of sensor options

Easy to use



Tetra 3

Specialist Four Gas Personal Monitor

Designed with the user in mind, the top mount display, full function data and event logs, audible, visual and vibrating alarms deliver top end performance in a small and lightweight package. Gases include the most common four (carbon monoxide, methane, oxygen and hydrogen sulfide), also an expanded range: ammonia, ozone, sulfur dioxide, hydrogen filtered carbon monoxide (for steel plants) hydrogen cyanide, other flammable gases and IR carbon dioxide (for safe area use only).



Robust

Rugged impact resistant design provides extra shock and vibration protection

Water and Dust resistant to IP65 and IP67

Can be submerged in water

Provides protection in the harshest environments

Effective warning

95 dB audible alarm

Vivid red/blue visual alarm

Vibrating alarm

Ensures clear warning facilitating prompt evacuations from hazard zones

Reliable

Proven sensor technology and software operation

Clear calibration-due warning

Lithium-ion battery provides 14 hours continuous operation from a single charge with no memory effects

Provides reliability you can trust and has the power to cover you for an extended shift

User friendly

Single button operation for all functions

Top mounted, backlit display of all gas readings, diagnostics and battery life

Can be operated with gloved hands

'At a glance' operating status

Product description

Single button operation, small size and clear top-mounted display make the T3 a favourite in the market amongst those working in today's most arduous industrial environments.



Gases and ranges

Gas	Range	Typical alarm (UK)
*Flammable	0- 100% LEL	20%
Oxygen (O ₂)	0-25%	19/23.5%
Hydrogen Sulfide (H ₂ S)	0-100ppm	5ppm
Carbon Monoxide (CO)	0-500ppm	30ppm
Sulfide dioxide (SO ₂)	0-20ppm	1ppm
Ozone (O ₃)	0-1ppm	0.1ppm
Ammonia (NH ₂)	0-100ppm	25ppm
**Carbon dioxide (CO ₂)	0-5%	0.5%
Carbon monoxide (CO) H ₂ compensated	0-500ppm	30ppm
Hydrogen Cyanide (HCN)	0-30ppm	10ppm

* Methane, Pentane, Propane, Butane, Ethylene, Hydrogen and others available, contact Crowcon for further options

** T3 is available in a safe area CO₂ version offering 0-5% carbon dioxide measurement. The CO₂ sensor replaces the flammable option and can be supplied with oxygen and toxic sensors.

Further gas types will be available - contact Crowcon with your requests.

Specification

Size		114 x 71 x 48mm (tapers to 20mm) (4.5 x 2.8 x 1.9ins)
Weight		295g (10.4oz)
Alarms	Audible	95dB multiple alarm sounds allow selection of distinctive tones for different alarm levels
	Vibrating	Internal vibrating alarm
Display	Main display	Graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), healthy operation or fault warning. Start up indication when calibration is due, overdue, or service required.
Display mode	Normal display	Real time gas concentration levels
	Display recall	Peak readings and TWA
Data logging	Timed datalogging	50 hours at 1-min data rate (>12,000 data logs of 4 channels)
	Threshold logging	Starts after adjustable pre-set level
	Event logging	>5,000 events
Battery		Rechargeable Li-ion battery
Operating time		Based on four-gas instrument fitted with flammable sensor: A 5 hour charge from flat provides at least 12 hours of continuous use. A 12-hr charge provides 14 hours of continuous use
Sampling		Diffusion or hand aspirator
Operating temp range		-20°C to +55°C (-4°F to +131°F)*
Humidity		15-95% RH non-condensing **
Ingress protection		IP65 and IP67
Certification	Europe	ATEX II 2G Ex db ia IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) Baseefa05ATEX0187
	International	IECEx Ex db ia IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) BAS05.0059
	North America	CSA Class I, Division 1 Groups A, B, C and D
Safety standards	Europe	EN60079-0, EN60079-11, EN60079-1, 2014/34/EU
	North America	CSA 22.2
	Operating standards	EN50270, EN50271, EN50104, EN45544, EN60079, IEC61508
PC interface		RS232 connection from interface module in charger RS232/USB converter available
Calibration		Can be routinely calibrated using Portables PC
Accessories		Integral alligator clip
Optional accessories		Universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing), fixed and telescopic sample probes, and an in-line water trap
Charging options		Single way drop-in charger with multi-region power supply (UK, USA, EU & Australian plug adaptors included) or inline 110V/220V supply; Single way drop-in charger with options as above including PC interface; 5 way multi-charger with universal power supply; Vehicle adapter for in-vehicle charging; Universal charger with status indication for vehicle, wall or desk mounting; can be used with multi region power supply or vehicle charging lead.

* Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods.

** Toxic and oxygen sensors RH specifications vary, consult Crowcon for specific operating humidities

Disclaimer

Every effort has been made to ensure the accuracy of this document at the time of printing. In accordance with the company's policy of continued product improvement Crowcon Detection Instruments Limited reserves the right to make product changes without notice. The products are routinely subject to a programme of testing which may result in some changes in the characteristics quoted. Technical information contained in this document or otherwise provided by Crowcon are based upon records, tests, or experience that the company believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed.

Many factors beyond Crowcon Detection Instruments' control and uniquely within user's knowledge and control can affect the use and performance of a Crowcon product in a particular application. As the products may be used by the client in circumstances beyond the knowledge and control of Crowcon Detection Instruments Limited, we cannot determine the relevance of these to an individual customer's application. It is the clients' sole responsibility to carry out the necessary tests to evaluate the usefulness of the products and review all applicable regulations and standards to ensure their safety of operation in a particular application.